

EXPRESSION





EXPRESSION 3120



EXPRESSION 3233



EXPRESSION 4110



EXPRESSION 4240



EXPRESSION 4241



EXPRESSION 4441



EXPRESSION 4544



EXPRESSION 5044



EXPRESSION 5130



EXPRESSION 5145



EXPRESSION 5550



EXPRESSION 6140



EXPRESSION 6240



EXPRESSION 6340



EXPRESSION 6540

Technical details carpet tiles

Manufacturing type	tufted 1/10"		
Construction			structured loop pile
Pile composition			100% PA 6
Dye method			solution dyed
Primary backing			polyester fleece
Secondary backing			GREENBASE modified bitumen
Pile weight	ISO 2424	g/m ²	650 (+/-)
Total weight	ISO 8543	g/m ²	4.300 (+/-)
Pile height	ISO 1766	mm	4,0 (+/-)
Total height	ISO 1765	mm	7,0 (+/-)
Tuft density	ISO 1763	/m ²	191.000 (+/-)
Size		cm	50 x 50
Packing			20 per box 5 m²
Classification	EN 1307		33 heavy commercial
Comfort rating	EN 1307		LC 1
Castor chair	EN 985		A intensive
Dimensional stability	EN 986		≤ 0,2%
Fire resistance	EN 13501-1		Bfl-S1 loose laid
Permanent antistatic	ISO 6356	kV	≤ 2,0
Transversal resistance	ISO 10965	Ω	≤ 10°
Thermal resistance	ISO 8302	m ² /K/W	0,066
Sound absorption	ISO 354	α _w	0,15
Impact sound reduction	ISO 10140	ΔL _w	25 dB
	ISO 10140	ΔL	42 dB (1000 Hz)
Light fastness	ISO 105 B02		≥ 6
Rubbing fastness	ISO 105 X12		4-5 wet/dry

